



TEGLA® Double Fit.

Versatile Glazing of Artwork with Dual Benefits.

TEGLA® Double Fit.

Advantages at a Glance

- Prevention of Newton-Rings (disturbing visual effects due to adhesion on glossy surfaces) by direct glazing
- Improved transparency and high color rendering, despite the double side structure
- Low reflection, no mirror effects
- Compared to single side structured picture framing products, no risk of confusion during glazing of your artwork
- Protection from dust, humidity and environmental influences
- Extremely durable and scratch-resistant glass surface
- Simple and easy cleaning

Specifications

- Premium float glass
- Double side structuring
- Cut edges, washed and paper interleaved

Technical Data

TEGLA® Double Fit

Glass thickness	2 mm (+0.2/-0.3 mm)
Weight	5 kg/m ²
Gloss value	80 (±15) – European gloss value measured at 20° (acc. DIN EN ISO 2813)
Residual reflection	1 %
Transmission	91 % total transmission (according to ASTM D 1003)
Haze	1 %
UV protection	45 % (300–380 nm)

Packaging, Transport and Storage

- Standard size available from stock
- Special sizes or packaging on request

Size	Box content (approx. 60 m ²)
1,600 x 1,020 mm	36 pieces

TEGLA® Double Fit is supplied in transport-safe wooden boxes with acid-free paper liners. In order to avoid humidity between the glass panels, the package is wrapped in plastic foil with a desiccant.

After opening the foil, storage under low humidity is required.

Handling

TEGLA® Double Fit is as easy to handle as ordinary float glass.

Cleaning Recommendation

Cleaning is done with commercial glass cleaners.

Caution. Do not use cleaners containing fluorides or hydroxides.